

# Suspended luminaire

VIVAA VTL C 600 D15515000

# Waldmann **W**

ENGINEER OF LIGHT.



**Derungs**   
LIGHT FOR PEOPLE

<b>fitted with</b>	6 x LED module - Energy efficiency category A+
<b>light distribution</b>	direct/indirect
<b>color rendering index (CRI)</b>	> 80
<b>colour temperatur</b>	3000-6500 K
<b>work equipment</b>	electronic converter
<b>connected load</b>	220-240V; 50/60Hz
<b>mains lead</b>	direct power supply
<b>luminaire body</b>	stainless steel
<b>weight (net)</b>	8.1 kg
<b>power consumption</b>	99 W
<b>luminous flux</b>	10700 lm
<b>luminous efficacy</b>	108 lm/W
<b>lamp cover</b>	CDP micro prismatic screen (PMMA)
<b>technology</b>	continuously dimmable
<b>class of protection</b>	I
<b>accessory</b>	module for light management, light decor foil
<b>norms</b>	EN 60598-1, EN 60598-2-25
<b>Room height</b>	270 - 300 cm, ceiling clearance 50 cm
<b>special features</b>	Suitable for screen work according to EN 12464-1, CDP micro prismatic screen, DALI version, Suitable for emergency lighting units according to EN 50172, visual timing light
<b>fastening</b>	ceiling fastening (pendel)
<b>glare-free</b>	prismatic screen
<b>system of protection</b>	IP 20
<b>order number</b>	D15515000 - Stainless steel/pure white

## light distribution

