



<b>fitted with</b>	8 x LED module
<b>work equipment</b>	Energy efficiency category A+
<b>connected load</b>	power supply unit
<b>power consumption</b>	220-240V; 50/60Hz
<b>power factor</b>	approx. 60 W
<b>luminous flux</b>	approx. 0,990
<b>light yield</b>	approx. 5800 lm
<b>light distribution</b>	approx. 97 lm/W
<b>direct ratio</b>	direct/indirect
<b>light colour</b>	approx. 44 %
<b>Color Rendering Index (CRI)</b>	neutralweiß, approx. 4000 K
<b>consistent white light of</b>	> 80
<b>glare-free</b>	< 3 SDCM
<b>luminance</b>	structured screen
<b>unified glare rating</b>	< 2300 cd/m <sup>2</sup>
<b>technology</b>	< 16
<b>usage</b>	continuously dimmable
<b>luminaire body</b>	external
<b>lamp cover</b>	aluminium, anodised, aluminium coloured anodised
<b>weight (net)</b>	acrylic clear
<b>mains lead</b>	approx. 6.6 kg
<b>fastening</b>	approx. 1.0 m; with free stranded wires
<b>special features</b>	steel cable 0.3 - 0.7 m
	DALI - dimming via digital rotary dimmer, integration into DALI light management systems, LED light engine according to Zhaga standard, light forming, TouchDIM - dimming via standard switch

## luminous intensity

Comment: Simulation

